

Test report

17-9679

Article:

Kaloo BP 550

Test requested by:

Jan Jismyr
Material AB
Tranås Sweden



Tests are carried out according to standard:

EN 16139:2013, test severity level 1

Discrepancies:

None

Result and observations:

The sample submitted for test fulfils the requirements in above mentioned standards.

Measurement:

Detailed information about measurement uncertainty is provided on request by Kinnarps Test and Verification Center.

Report:

This report relates to sample submitted for test and no other. The report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Kinnarp 6th of February 2017



Daniel Landberg
(Approved by)



Susanne Norling
(Tested by)

Item description

Date of

- **manufacture:** 161216
- **arrival:** 170111
- **test:** 170116 - 170206

Materials, construction Steel tube with seat of upholstered plywood

Dimensions (mm)

Total width:	575	Sitting height:	760
Total depth:	545	Seat width:	400
Total height:	1000	Seat depth:	400
Seat height:	420	Height of armrest:	180
Weight (kg):	7,3kg	Distance between armrests:	500

Test conditions

Laboratory atmosphere: (20 ± 5)° C Within limits during test

Test description

EN 16139:2013 Annex B (informative)

The table below shows the type of use that might be expected from furniture in relation to two test severities.

Test severity	Type of Use	Application
L1	General use	Areas in which seating is usually intended for mixed use (short-time and for a period of several hours, light to heavy load). Example of end-use: All kind of applications in office buildings, showrooms, public halls, function rooms, cafés, restaurants, canteens, banks, bars.
L2	Extreme use	Areas in which seating is occasionally or repeatedly subject to extremely high loads due to their specific types of use or due to improper use. Examples of end-use: Night -clubs, police stations, transport terminals, sport changing rooms, prisons, barracks (non-controlled areas).

It should be noted that some end uses may be covered by more than one requirement depending on the severity of the expected use.

This applies particularly to furniture in nursing homes and public areas in hospitals. These types of furniture are subject to test severity L1. But for seating fulfilling the requirements "Seating which may be moved when occupied", the test "Vertical upwards static load on arm rests" in accordance with Table 1 (Test 7) should be carried out with test severity L2.

Test and method	Requirements	Test results	Pass/Fail or N/A
SAFETY EN 16139:2013 4			
General 4.1			
Accessible corners	a) shall be rounded or chamfered	No remarks	Pass
Edges of seat, back and arm rests, which are in contact with the user when sitting in the seating	b) shall be rounded or chamfered	No remarks	Pass
Edges of handles	c) shall be rounded or chamfered in the direction of the force applied	No remarks	Pass
All other edges accessible during use	d) no rough surfaces, burrs or sharp edges	No remarks	Pass
End of hollow components	e) closed or capped	No remarks	Pass
Movable and adjustable parts designed so	injures and inadvertent operations shall be avoided	-	N/A
Adjustable/connection parts	no chance to come loose	-	N/A
Lubricated parts	not accessible	-	N/A
Shear and squeeze points		-	N/A
STABILITY 4.3			
Non swivelling chairs 4.3.3			
Forward Vertical force 600 N	horizontal min. 20 N no overturning	94N	Pass
Sideways without arm rests Vertical force 600 N	horizontal min. 20 N no overturning	-	N/A
Sideways with arm rests Vertical force on seat 250 N Vertical force on armrest 350 N	horizontal min. 20 N no overturning	46N	Pass
Rearward Vertical force 600 N	horizontal min. 68 N no overturning	146	Pass
Forwards overturning for seating with footrest Vertical force on the footrest 600 N	horizontal min. 20 N no overturning	-	N/A
Rolling resistance of the unloaded chair 4.4		-	N/A

EN 16139: 2013 5. Safety, strength and durability requirements

These safety, strength and durability requirements are fulfilled when during and after testing:

- a) There are no fractures of any member, joint or component;
- b) There are no loosening of joints intended to be rigid;
- c) No major structural element is significantly deformed;
- d) The chair fulfils its functions after removal of the test loads.

Test and method		Requirements		Test results	Pass/Fail or N/A
		Level 1	Level 2		
STRENGTH AND DURABILITY					
EN 16139:2013 5					
Seat and back static load	10 times, vertical force horizontal force	1 600 N 560 N (min. force 410)	2 000 N 700 N (min. force 410)	No remarks	Pass
Seat front edge static load	10 times, vertical force	1 300 N	1 600 N	No remarks	Pass
Vertical static load on back.	10 times, vertical force seat load	600 N 1300 N	900 N 1800 N	No remarks	Pass
Foot rail / foot rest and leg rest static load	10 times, force	1 300 N	1 600 N	No remarks	Pass
Arm sideways static load between armrests	10 times, horizontal force	400 N	900 N	No remarks	Pass
Arm downwards static load	5 times, vertical force	750 N	900 N	No remarks	Pass
Vertical upwards static load on armrests	10 times	Seat load 250 N or lift stack	Seat load 1 200 N	-	N/A
Seat and back fatigue	Cycles vertical force horizontal force	100 000 c 1 000 N 300 N	200 000c 1 000 N 300 N	No remarks	Pass
Seat front edge fatigue	Cycles vertical force	50 000 c 800 N	100 000c 800 N	No remarks	Pass
Arm fatigue	Cycles force	30 000 c 400 N	60 000c 400 N	No remarks	Pass
Foot rest/foot rail fatigue	Cycles force	50 000 c 1000 N	1 00 000c 1000 N	No remarks	Pass
Leg forward static load <small>If the item tends to overturn, reduce the force to a magnitude that just prevents overturning</small>	10 times, force seat load	500 N 1 000 N	620 N 1 800 N	No remarks	Pass
Leg sideways static load <small>If the item tends to overturn, reduce the force to a magnitude that just prevents overturning</small>	10 times, force seat load	400 N 1 000 N	760 N 1 800 N	No remarks	Pass
Seat impact test	10 times, Drop height	240 mm	300 mm	No remarks	Pass

Test and method		Requirements		Test results	Pass/Fail or N/A
		Level 1	Level 2		
Back impact test (test for heavy chair)	10 times Height of fall	210mm/38°	330 mm/48°	-	N/A
Arm impact test	10 times Height of fall	210mm/38°	330 mm/48°	No remarks	Pass
Drop test (multiple seating)	2x5 times Drop height	Not applicable	450mm	-	N/A
Auxiliary writing surface Static load test	10 times Force	300 N	300 N	-	N/A
Auxiliary writing surface fatigue	Cycles Force	10 000c 150 N	20 000c 150 N	-	N/A
Additional test for specific applications EN 16139:2013 Annex A.1 (informative)					
Drop test for stacking seating	10 times Drop height	150 mm	200 mm	-	N/A
Backward fall test (test for light chair)	Times	5	5	No remarks	Pass
Drop test from the height of a table10 times (5 times on one front leg and 5 times on one rear leg)	Drop height	600 mm	600 mm	-	N/A
<p>EN 16139:2013 7. Information for use Information for use shall be available in the language of the country in which it will be delivered to the end user. It shall contain at least the following details:</p> <ul style="list-style-type: none"> a) Information regarding the intended use (see Annex B); b) If the chair is fitted with adjusting mechanisms: instruction for operating the adjusting mechanism; c) Assembly instructions, where applicable; d) Instruction for the care and maintenance of the chair; e) If the seating is fitted with castors: information on the choice of castors in relation to the floor surface. 					

End of report